



## Self-Contained Autoclave for Investment Casting

### SALIENT FEATURES :

- Electrically Heated with optional Gas or Oil versions available.
- Economical, Efficient and Easy to Maintain.
- No Fractured Shells due to Instant Thermal Transfer.
- Simple to Install.
- Connect Services & Start Dewaxing.
- Logical State of the Art Control Systems.
- Controllable Pressurisation and De-Pressurisation Cycle.
- Automatic Wax Drain System using Residual Steam Pressure, available as an option.
- Energypack 'Secure Door' Door Locking System.
- Excellent Heat Retention Properties due to Unique Heat Insulation.

## Self-Contained Autoclave for Investment Casting



**Five Standard Models of Dewaxing Autoclave are available, Either a Self-Contained Unit with Inbuilt Boiler or with a Separate Free Standing Boiler**

Model	Diameter	Length	Pressure	Heaters for Electrical Heating	Oil Consumption for External Steam Generation Unit
	mm	mm	Kgs./cm <sup>2</sup>	KW	Kgs./hr.
EBPL-DAC-9/10	900	1000	10	75	12
EBPL-AC-10/13	1000	1300	10	96	18
EBPL-DAC-11/15	1100	1500	10	120	24
EBPL-DAC-13/15	1300	1500	10	144	24
EBPL-DAC-20/30	2000	3000	10	180	30

**Energypack Autoclaves are Purpose built for Dewaxing Investment Casting Shells**